Note: Footing #4 poured 8'-8" x 15'-8".
Footing #5 poured 8'-8" x 15'-10".

16'-0"

B. of F + 9.62

7 Rods

5 Rods

B. of F + 6.62

8'-0"

4'-0"

8'-8"

15'-0"

7'-6"

3'-6"

Inside line of Brick Wall

B. of F + 12.04

17 Rods

Footing 8' wide x 16' long

22'-1½"

Opening for Stair

15"x15" Hole Top at El 13.50

15"x15" Hole Top at El 14.75

Opening 24" Wide x 18" High. Top at El +13.50

22'-3½"

22'-8"

6'-0"

4'-0"

15'-1"

Note: At doorways stop all footing walls (top at El +15.50) at El. +15.50.

Top of footing at El. +15.50. Slab to be 8½" thick

4'-0"

2'-0"

2'-0"

4-1½"ϕ x 8" lg. Bolts - 2" thread exposed - on 9" dia. Bolt Circle [Use template]

5'-0"

3'-6"

1½"ϕ bolts - 6" o.c. 7" from top of footing

10-1/2" C. to C. of Columns

PLAN VIEW OF FOOTING FOR SPIRAL STAIR

Openings 15" sq. - Elev. of top + 15.00 Reinforce around openings

El +9.62

Section

This is poured

Note: The Elev. of this footing to be checked in field.

Check cont. of Block line of Slot

Bott. of Base Pl. Elt 13.12

1'-10"

1'-0" Grout

3'-0"

10"

Footing 8' wide x 16' long

Inside line of Brick Wall

Opening for Stair

For location of openings see Sht #487

Brick Pilasters

Footing for